

DEVELOP


Dynamic balance

www.develop.eu



ineo 4052

- > Black & white
A4 multifunctional
- > Up to 40 ppm



Finishing functionalities



Corner stapling



Duplex

ineo 4052

A4 multifunctional with 40 ppm b/w. Standard ineo print controller with PCL, PostScript and XPS support. Paper capacity of 550 sheets and 100-sheet manual bypass. Automatic dual-scan document feeder and duplex unit standard. 2 GB memory, 250 GB hard disk and Gigabit Ethernet.

| | |
|---------------------------------------|--|
| PF-P15 Paper tray | A5–A4, 250 sheets, 60–120 g/m ² |
| PF-P16 Paper tray | A5–A4, 550 sheets, 60–120 g/m ² |
| SCD-4000e Copier desk | Provides storage space for print media, etc. |
| FS-P02 Staple finisher | 20-sheet corner stapling |
| FK-517 Fax kit | Super G3 fax; digital fax functionality |
| KP-101 10-Key pad | For use instead of touchscreen |
| EK-P05 USB I/F kit | USB keyboard connection |
| EK-P06 USB I/F kit | USB keyboard connection, Bluetooth |
| EK-P07 Interface cable for CSRC modem | GPRS modem connection for CSRC |

| | |
|---------------------------------|---|
| AU-102 Biometric authentication | Finger vein scanner |
| ID card reader | Various ID card technologies |
| LK-102v3 PDF enhancements | PDF/A (1b), PDF encryption, digital signature |
| LK-106 Barcode fonts | Supports native barcode printing |
| LK-107 Unicode fonts | Supports native Unicode printing |
| LK-108 OCR A and B fonts | Supports native OCR A and B font printing |
| LK-111 ThinPrint® Client | Print data compression for reduced network impact |
| LK-114 Serverless Pull Printing | Secure and Follow Me printing solution require no server application. Host devices require 4 GB memory. |
| LK-115v2 TPM activation | Trusted Platform Module for protection of data encryption and decryption |
| UK-219 Upgrade kit | 2 GB memory extension for upgrades |
| UK-216 Wireless LAN | Wireless LAN and wireless LAN Access Point Mode |
| SX-BR-4600 Wireless LAN | Wireless LAN to network connector |
| CU-203 Air cleaning unit | Improving indoor air quality by reduced emissions |

Technical specifications

SYSTEM SPECIFICATIONS

| | |
|-------------------------------------|---|
| Panel size/resolution | 7" / 800 x 480 |
| System memory (standard/max) | 2 GB/4 GB |
| System hard disk | 250 GB (standard) |
| Interface | 10/100/1,000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11b/g/n (optional) |
| Network protocols | TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP; HTTPS |
| Automatic document feeder | Up to 50 originals; A6–A4; 52–120 g/m ² ; automatic dualscan document feeder |
| Printable paper size | A6–A4; customised paper sizes |
| Printable paper weight | 60–216 g/m ² |
| Paper input capacity (standard/max) | 650 sheets/2,300 sheets |
| Paper tray input (standard) | 550 sheets; A6–A4, 60–120 g/m ² |
| Paper tray input (optional) | 3x 250/550 sheets; A5–A4; 60–120 g/m ² |
| Manual bypass | 100 sheets; A6–A4; custom sizes; 60–216 g/m ² |
| Automatic duplexing | A4; 60–90 g/m ² |
| Finishing modes | Group/sort; staple (optional) |
| Output capacity | Max.: 250 sheets |
| Stapling (optional) | Max.: 20 sheets |
| Copy/print volume (monthly) | Rec.: 7,000 pages Max.: 100,000 pages |
| Toner lifetime | 25,000 pages |
| Imaging unit lifetime | 60,000 pages |
| Power consumption | 220–240 V/50/60 Hz; Less than 600 W |
| System dimensions (W x D x H) | 490 x 521 x 546 mm |
| System weight | Approx. 24 kg (without options) |

COPIER SPECIFICATIONS

| | |
|---------------------|---|
| Copying process | Electrostatic laser |
| Copy/print speed A4 | Up to 40 ppm |
| Autoduplex speed A4 | Up to 30 ppm |
| 1st copy out time | 6.5 sec. |
| Copy resolution | 600 x 600 dpi |
| Gradation | 256 gradations |
| Multicopy | 1–9,999 |
| Original format | Max. A4 |
| Magnification | 25–400% in 0.1% steps; auto-zooming |
| Copy functions | Electronic sorting; multi-job; adjustments (contrast, sharpness, image density); proof copy; interrupt mode; separate scan; sort/group; combination; original selection; ID card copy; 2-in-1; 4-in-1; 8-in-1 |

PRINTER SPECIFICATIONS

| | |
|---------------------------|---|
| Print resolution | 600 x 600 dpi; 1,200 x 1,200 dpi |
| Page description language | PCL 6 (XL 3.0); PCL 5; PostScript 3 (CPSI 3016); XPS |
| Operating systems | Windows 7 (32/64); Windows 8 /8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Macintosh OS X 10.9 or later; Linux; Unix |
| Printer fonts | 80 PCL Latin; 137 PostScript 3 Emulation Latin |
| Print functions | Direct print of TIFF; XPS; PDF (v1.7) and OOXML (DOCX, XLSX, PPTX); secure print; proof print; overlay; n-up; booklet page order; watermark |
| Mobile Printing | AirPrint (iOS), Mopria (Android), ineoPRINT (iOS/Android/Windows 10 Mobile); Mobile Authentication and Pairing (Android & iOS) optional: Google Cloud Print; Wifi Direct |

SCANNER SPECIFICATIONS

| | |
|--------------------------|--|
| Scan speed (mono/colour) | Up to 47/30 ipm in simplex Up to 94/60 ipm in duplex |
| Scan resolution | Up to 600 x 600 dpi |
| Scan modes | Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home); Scan-to-FTP; Scan-to-HDD; Scan-to-USB; Scan-to-WebDAV; Scan-to-URL; Network TWAIN scan |
| File formats | TIFF, PDF, Compact PDF, JPEG, XPS, PDF/A (opt.), Compact XPS, PPTX, Linearized PDF, Encrypted PDF |
| Scan destinations | 2,100 (single + group); LDAP support |
| Scan functions | Up to 400 job programs |

FAX SPECIFICATIONS

| | |
|-------------------------|---|
| Fax standard | Super G3 (optional) |
| Fax transmission | Analogue; i-Fax |
| Fax resolution | Up to 600 x 600 dpi (ultra-fine) |
| Fax compression | MH; MR; MMR; JBIG |
| Fax modem | Up to 33.6 Kbps |
| Fax destinations | 2,100 (single + group) |
| Fax functions | Time shift; PC-Fax; fax forwarding; up to 400 program dials |

SYSTEM FEATURES

| | |
|-------------------|---|
| Security | ISO15408 Common Criteria (in evaluation); IP filtering and port blocking; SSL2; SSL3 and TLS1.0 network communication; IPsec support; IEEE 802.1x support; user authentication; secure print; Kerberos; hard disk overwrite (8 standard types); hard disk data encryption; copy protection (print only) |
| Accounting | Up to 1,000 user accounts; Active Directory support ID card authentication optional |
| Software | store+find (opt.); convert+share (opt.); Personal Applications (opt.); Device Manager (opt.); Data Administrator (user accounts & cost centres); Card solutions (opt.); Unix/Linux support; SAP support; EveryonePrint (opt.) |



DEVELOP

Konica Minolta Business Solutions Europe GmbH
 Europaallee 17 30855 Langenhagen Germany Phone +49 511 7404-0 www.develop.eu

For more information regarding the ineo 4052 please refer to the respective product homepage



- All specifications refer to A4-size paper of 80 g/m² quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- DEVELOP and ineo are registered trademarks/product titles owned by Konica Minolta Business Solutions Europe GmbH.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.